



CE Marking of Float glass - EN 572-9:2004
Declaration of performances
Planibel Bronze (annealed)



We

AGC Glass Europe
Building Division

Chaussée de La Hulpe 166 - B 1170 Brussels
 Tel.: + 32 - (0) 2 674.31.11 - Fax: + 32 - (0) 2 674.44.62

Declare, under his sole responsibility, the following characteristics for the CE Marking of the glass products named **PLANIBEL BRONZE**, intended to be used in buildings and construction works, following **EN 572-9:2004**

	Planibel Bronze characteristics in :	AVCP Systems	3 mm	4 mm	5 mm	6 mm	8 mm	10 mm
1.	Resistance to fire (EN 13501-2)	1	NPD	NPD	NPD	NPD	NPD	NPD
2.	Reaction to fire (EN 13501-1)	3, 4	A1	A1	A1	A1	A1	A1
3.	External fire performances	3, 4	NPD	NPD	NPD	NPD	NPD	NPD
4.	Bullet resistance (EN 1063)	1	NPD	NPD	NPD	NPD	NPD	NPD
5.	Explosion resistance (EN 13541)	1	NPD	NPD	NPD	NPD	NPD	NPD
6.	Burglar resistance (EN 356)	3	NPD	NPD	NPD	NPD	NPD	NPD
7.	Pendulum body impact resistance (EN 12600)	3	NPD	NPD	NPD	NPD	NPD	NPD
8.	Resistance against sudden temperature change and temperature differentials	4	NPD	NPD	NPD	NPD	NPD	NPD
9.	Wind, snow, permanent and imposed load resistance	4	NPD	NPD	NPD	NPD	NPD	NPD
10.	Direct airborne sound reduction (EN 12758): R_w (C;Ctr)	3	29 (-2;-5)	30 (-2;-4)	30 (-1;-2)	31 (-2;-3)	32 (-1;-2)	34 (-2;-3)
11.	- U-value (EN 673) - Normal emissivity ϵ_n coated side (EN 12898)	3	5,8 0,89	5,8 0,89	5,8 0,89	5,7 0,89	5,7 0,89	5,6 0,89
12.	Light transmission/reflection (EN 410): $\tau_v / \rho_v / \rho'_v$	3	68 / 6 / 6	62 / 6 / 6	56 / 6 / 6	51 / 6 / 6	41 / 5 / 5	34 / 5 / 5
13.	- Solar transmission/reflection/factor (EN 410): $\tau_e / \rho_e / \rho'_e$ - Solar factor: g	3	67 / 6 / 6 74	61 / 6 / 6 69	56 / 6 / 6 65	50 / 5 / 5 61	42 / 5 / 5 54	34 / 5 / 5 49
14.	Durability	3	PASS	PASS	PASS	PASS	PASS	PASS

Brussels
 14th of June 2013

E. Ceriani
 Primary Sales & Strategic, Marketing Director, Building